

Features of Boom Sprayer...

- 24 ft. single-side boom that provides a 50 ft. coverage pattern between drive rows. Up to 60 ft. with spray gun at end of boom.
- Easy, 60 second, manual boom height adjustment from 2 ft. for melons to 7.5 ft. for sweet corn.
- Hydraulic on-the-go boom leveling allows operator to maintain uniform height between boom and the crop.
- Pump driven with PTO power shaft for quick hookup.
- Adjustable wheel spacing, tongue height and control holder.
- Boom protected by rubber shock-absorber mounting.
- Disc Core spray tips for best foliage contact when spraying insecticides and fungicides.
- Top quality John Blue 215 PSI, 28 GPM diaphragm pump.
- 200 gallon trailer models F224
- 300 gallon trailer models F324
- 400 gallon trailer models F424
- Off-the-shelf parts that are readily available from our parts stock, or from Hypro and Teejet parts suppliers.
 John Blue control valves with liquid-filled pressure gauge.
- Dual agitators with throttle valve requires no premixing of chemicals.
- 560 PSI pressure hose.









- 1. Shock-absorber
- 2. John Blue Pump
- 3. Remote Control Valve
- 4. Rinse Tank Faucet







Optional Rinse Tank

Sprayer Options...

- Rinse tank to clean sprayer in field
- Spray gun at end of boom to extend spray coverage to 30 ft.
- Rear boom to spray track row



Call (570) 837-1197 And let's talk sprayers!

PENNS CREEK WELDING LLC

Ben Oberholtzer • 1340 Broadway Road, Winfield, PA 17889 www.pennscreekwelding.com